

SK700-II LPG COMBI & ADD ON

A modular and versatile solution

- > Lane orientation
- > Up to 10 hoses
- > LPG plus up to four standard fuel grades
- > External or internal hose with retraction



Product specifications

The Sk700-II LPG Combi allows for LPG plus up to five additional grades to be delivered from the one dispenser. Up to two additional fuel grades in a single compact hydraulic cabinet or up to five additional grades in an add-on cabinet.

| Technical Specifications | Standard Features | Options |
|--------------------------|---|--|
| Hydraulics | LPG hydraulics with 1 or 2 meters Electronic meter calibration Break away coupling — Elaflex | Solenoid valve: two stage dual flow for pre-set Shear valve |
| Electronics | Pulser Calculator LCD display (back lit) Dead man push button | Emergency stop button Automatic Temperature Compensation (selected countries) Pre set keypad Computer head door alarm Bolt-on CRIND ready Communication protocol options Electromechanical totaliser |
| Mechanical | Housing — painted steel Frame — hot galvanized sheet metal Hose Management — internal hose connection CR LPG nozzle — T3 OPW Hose — Elaflex | Stainless steel hose column and hydraulic panels Livery options on request Types of nozzles on request Nozzle lock Hose management system: external hose with rope retract |

Technical Characteristics & Performance

| | |
|-----------------------|--|
| Environmental | Climate: Marine, tropical, industrial, polar Ambient temperature range: -25°C to +50°C |
| Meter characteristics | Displacement: 0,500L Maximum flow rate: 50L/min Minimum flow rate: 5L/min Accuracy within the flow range: ± 1% Maximum service pressure (operating pressure): 25 bar |
| Electrical | 230V (+10%; -15%), 50Hz ± 2Hz |

